

**FREE FLIGHT ENTERPRISES  
LARA SPEC SHEET**

MODEL	GORES	ITEM WEIGHT (LBS)	CONSTRUCTION DIAMETER (FT)	SQ FT	PILOT WEIGHT MAX (LBS)	LINES, SUSP, VENT, CENTER (LBS)	BRIDLE / RISER BREAKING STRENGTH (LBS)
L.A.R.A. 175, HG*	20	5.3	15.0	294.0	175	NYLON 400, 360, 2000	NYLON 6,000
L.A.R.A. 175 GOLD, HG*	20	4.7	15.0	294.0	175	SEPCTRA 500, 500, 2000	KEVLAR 6,000
L.A.R.A. 175, PG*	20	5.1	15.0	294.0	175	NYLON 400, 360, 2000	NYLON 6,000
L.A.R.A. 175 GOLD, PG*	20	3.8	15.0	294.0	175	SEPCTRA 500, 500, 2000	KEVLAR 6,000
L.A.R.A. 250, HG*	22	5.8	16.0	328.0	250	NYLON 400, 360, 2000	NYLON 6,000
L.A.R.A. 250 GOLD, HG*	22	4.7	16.0	328.0	250	SEPCTRA 500, 500, 2000	KEVLAR 6,000
L.A.R.A. 250, PG*	22	5.6	16.0	328.0	250	NYLON 400, 360, 2000	NYLON 6,000
L.A.R.A. 250 GOLD, PG*	22	4.1	16.0	328.0	250	SEPCTRA 500, 500, 2000	KEVLAR 6,000
L.A.R.A. 400, HG*	24	10.0	20.0	503.0	400	NYLON 400, 360, 2000	KEVLAR 13,500
L.A.R.A. 400 GOLD, HG*	24	7.8	20.0	503.0	400	SEPCTRA 500, 500, 2000	KEVLAR 13,500
L.A.R.A. 400, PG*	24	9.5	20.0	503.0	400	NYLON 400, 360, 2000	KEVLAR 13,500
L.A.R.A. 400 GOLD, PG*	24	6.8	20.0	503.0	400	SEPCTRA 500, 500, 2000	KEVLAR 13,500

\*ADD 1 LB IN ITEM WEIGHT FOR THE PARASWIVEL ON THE L.A.R.A. AND P.D.A.